

Safety isolating transformer

FLE 12/9 Discontinued line - not for new designs



Picture shows FLE 35/6


Advantages

| |
|--|
| Minimum size at high output |
| Low height |
| Integrated overload protection using PTC in the input |
| Double output voltage for series or parallel connection |
| Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation |
| Self-extinguishing potting material |

Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Safety isolating transformer
to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals



VDE



Safety isolating transformer FLE 12/9 Discontinued line - not for new designs

| Type | | FLE 12/9 Discontinued line - not for new designs |
|-------------------------|--|--|
| Electrical data | Input | |
| | Rated input voltage | 230 Vac |
| | Rated frequency | 50 - 60 Hz |
| | Output | |
| | Rated output voltage | 2 x 9 Vac |
| | Rated Power | 12 VA |
| | No-load voltage (app. x factor) | 1.31 |
| | No-load loss (typ.) | 1.80 W |
| | Efficiency | 73.0 % |
| | Standards | |
| | Classification | Safety isolating transformer |
| | Approvals | |
| | Approvals | VDE |
| | Environment | |
| | Ambient temperature max. | 40 °C |
| | Safety and protection | |
| Type | Encapsulated | |
| Insulation class | E | |
| Protection index | IP 00 | |
| Safety class (prepared) | II | |
| Short circuit strength | non-inherently short-circuit proof | |
| Order numbers | | |
| Order Number | FLE 12/9 Discontinued line - not for new designs | |

| Type | | FLE 12/9 Discontinued line - not for new designs |
|-----------------|-----------------------|--|
| Mechanical data | Terminal and mounting | Pins for PCB |
| | Measures and weights | |
| | Core type | UI 39/13,5 |
| | Weight | 0.37 kg |

