

Safety isolating transformer

FLE 6/15 Discontinued line - not for new designs



Picture shows FLE 35/6


Advantages

Minimum size at high output
Low height
Integrated overload protection using PTC in the input
Double output voltage for series or parallel connection
Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation
Self-extinguishing potting material

Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Safety isolating transformer
to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals



VDE




Safety isolating transformer

FLE 6/15 Discontinued line - not for new designs

Type		FLE 6/15 Discontinued line - not for new designs
Electrical data	Type	
	Input	
	Rated input voltage	230 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 15 Vac
	Rated Power	6 VA
	No-load voltage (app. x factor)	1.33
	No-load loss (typ.)	1.30 W
	Efficiency	72.0 %
	Standards	
	Classification	Safety isolating transformer
	Approvals	
	Approvals	VDE
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Type	Encapsulated
Insulation class	E	
Protection index	IP 00	
Safety class (prepared)	II	
Short circuit strength	non-inherently short-circuit proof	
Order numbers		
Order Number	FLE 6/15 Discontinued line - not for new designs	

Type		FLE 6/15 Discontinued line - not for new designs
Mechanical data	Terminal and mounting	
	Terminals	Pins for PCB
	Measures and weights	
Core type	UI 30/16,5	
Weight	0.25 kg	



Subject to change.