

Motor filter MF Range

**MF 400/4 - no longer available**

---

Standards

---

Approvals

---

# Motor filter MF Range

## MF 400/4 - no longer available

Type		MF 400/4 - no longer available	Type		MF 400/4 - no longer available	
Electrical data	Operating data		Terminal and mounting			
	for inverter output approx.	2.70 kVA	Fixing method	Mounting lugs		
	for motor rated output approx.	1.50 kW	Fixing screws	M6		
	Inverter load	add. with approx. 12 % of rated current	Terminals	Screw-type terminals		
	Max. length of motor lead	100m=4kHz, 50m=8kHz, 25m=16kHz	Measures and weights			
	Rated current	3 x 4 A	Weight	4.30 kg		
	Input					
	Rated frequency	0 - 150 Hz				
	Operating data					
	Rated voltage	3 x 400 Vac				
	Voltage drop	7.5				
	Voltage range	0 - 3 x 510 Vac				
	Switching frequency	4 - 16 kHz				
	Environment					
	Ambient temperature max.	40 °C				
	Safety and protection					
	Protection index	IP 00				
Safety class (prepared)	I					
Type	Metal enclosure					
Order numbers						
<b>Order Number</b>	<b>MF 400/4 - no longer available</b>					

30  
Mechanical data

Subject to change.