

Toroidal safety isolating and isolating transformer RK Range
RK 15/15 - no longer available



RK 100/25

Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 15/15 - no longer available**

| Type | RK 15/15 - no longer available |
|---------------------------------|---------------------------------------|
| Electrical data | |
| Input | |
| Input rated voltage | 2 x 115 V |
| Low-inrush current | 11-times |
| Rated frequency | 50 - 60 Hz |
| Output | |
| Efficiency | 83.0 % |
| No-load loss (typ.) | 0.30 W |
| No-load voltage (app. x factor) | 1.20 |
| Output rated voltage | 2 x 15 V |
| Rated Power | 15.0 VA |
| Approvals | |
| Approvals | UL, C-UL |
| Environment | |
| Ambient temperature max. | 40 °C |
| Safety and protection | |
| Insulation class | A |
| Protection index | IP 00 |
| Safety class (prepared) | II |
| Test voltage | 4000 V, 50 Hz |
| Type | Open type |
| Catalogue logic | |
| Order numbers | |
| Order Number | RK 15/15 - no longer available |

| Type | RK 15/15 - no longer available |
|------------------------------|--------------------------------|
| Mechanical data | |
| Terminal and mounting | |
| Fixing method | Central connection by bolt |
| Fixing screws | M5 |
| Terminals | leads |
| Measures and weights | |
| Diameter Ø | 62 mm |
| Weight | 0.30 kg |