

Toroidal safety isolating and isolating transformer RK Range
RK 160/12 - no longer available



Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 160/12 - no longer available**

Type		RK 160/12 - no longer available	Type		RK 160/12 - no longer available
Electrical data	Input		Mechanical data	Terminal and mounting	
	Input rated voltage	2 x 115 V		Fixing method	Central connection by bolt
	Low-inrush current	25-times		Fixing screws	M6
	Rated frequency	50 - 60 Hz		Terminals	leads
	Output			Measures and weights	
	Efficiency	90.0 %		Diameter Ø	108 mm
	No-load loss (typ.)	2.00 W		Weight	1.50 kg
	No-load voltage (app. x factor)	1.10			
	Output rated voltage	2 x 12 V			
	Rated Power	160.0 VA			
	Approvals				
	Approvals	UL, C-UL			
	Environment				
	Ambient temperature max.	40 °C			
	Safety and protection				
	Insulation class	A			
	Protection index	IP 00			
Safety class (prepared)	II				
Test voltage	4000 V, 50 Hz				
Type	Open type				
Catalogue logic					
Order numbers					
Order Number	RK 160/12 - no longer available				

Subject to change.