

Toroidal safety isolating and isolating transformer RK Range **RK 160/15 - no longer available**



Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 160/15 - no longer available**

Type	RK 160/15 - no longer available
Electrical data	
Input	
Input rated voltage	2 x 115 V
Low-inrush current	25-times
Rated frequency	50 - 60 Hz
Output	
Efficiency	90.0 %
No-load loss (typ.)	2.00 W
No-load voltage (app. x factor)	1.10
Output rated voltage	2 x 15 V
Rated Power	160.0 VA
Approvals	
Approvals	UL, C-UL
Environment	
Ambient temperature max.	40 °C
Safety and protection	
Insulation class	A
Protection index	IP 00
Safety class (prepared)	II
Test voltage	4000 V, 50 Hz
Type	Open type
Catalogue logic	
Order numbers	
Order Number	RK 160/15 - no longer available

Type	RK 160/15 - no longer available
Mechanical data	
Terminal and mounting	
Fixing method	Central connection by bolt
Fixing screws	M6
Terminals	leads
Measures and weights	
Diameter Ø	108 mm
Weight	1.50 kg