

Toroidal safety isolating and isolating transformer RK Range  
**RK 25/12 - no longer available**



RK 100/25

## Standards

**Mains transformer**

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

**Safety isolating transformer**

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

**Isolating transformer**

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

## Approvals

UL 5085-1/-2, CSA 22.2 No.66



## Toroidal safety isolating and isolating transformer RK Range **RK 25/12 - no longer available**

Type		RK 25/12 - no longer available	
<b>Electrical data</b>	<b>Input</b>		
	Input rated voltage	2 x 115 V	
	Low-inrush current	16-times	
	Rated frequency	50 - 60 Hz	
	<b>Output</b>		
	Efficiency	82.0 %	
	No-load loss (typ.)	0.50 W	
	No-load voltage (app. x factor)	1.20	
	Output rated voltage	2 x 12 V	
	Rated Power	25.0 VA	
	<b>Approvals</b>		
	Approvals	UL, C-UL	
	<b>Environment</b>		
	Ambient temperature max.	40 °C	
	<b>Safety and protection</b>		
	Insulation class	A	
Protection index	IP 00		
Safety class (prepared)	II		
Test voltage	4000 V, 50 Hz		
Type	Open type		
<b>Catalogue logic</b>			
<b>Order numbers</b>			
<b>Order Number</b>	<b>RK 25/12 - no longer available</b>		

  

Type		RK 25/12 - no longer available	
<b>Mechanical data</b>	<b>Terminal and mounting</b>		
	Fixing method	Central connection by bolt	
	Fixing screws	M5	
	Terminals	leads	
	<b>Measures and weights</b>		
	Diameter Ø	68 mm	
Weight	0.40 kg		

Subject to change.