

Toroidal safety isolating and isolating transformer RK Range  
**RK 25/22 - no longer available**



RK 100/25

## Standards

**Mains transformer**

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

**Safety isolating transformer**

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

**Isolating transformer**

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

## Approvals

UL 5085-1/-2, CSA 22.2 No.66



## Toroidal safety isolating and isolating transformer RK Range **RK 25/22 - no longer available**

Type	RK 25/22 - no longer available
<b>Electrical data</b>	
<b>Input</b>	
Input rated voltage	2 x 115 V
Low-inrush current	16-times
Rated frequency	50 - 60 Hz
<b>Output</b>	
Efficiency	82.0 %
No-load loss (typ.)	0.50 W
No-load voltage (app. x factor)	1.20
Output rated voltage	2 x 22 V
Rated Power	25.0 VA
<b>Approvals</b>	
Approvals	UL, C-UL
<b>Environment</b>	
Ambient temperature max.	40 °C
<b>Safety and protection</b>	
Insulation class	A
Protection index	IP 00
Safety class (prepared)	II
Test voltage	4000 V, 50 Hz
Type	Open type
<b>Catalogue logic</b>	
<b>Order numbers</b>	
<b>Order Number</b>	<b>RK 25/22 - no longer available</b>

Type	RK 25/22 - no longer available
<b>Mechanical data</b>	
<b>Terminal and mounting</b>	
Fixing method	Central connection by bolt
Fixing screws	M5
Terminals	leads
<b>Measures and weights</b>	
Diameter Ø	68 mm
Weight	0.40 kg