

Toroidal safety isolating and isolating transformer RK Range
RK 25/6 - no longer available



RK 100/25

Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 25/6 - no longer available**

Type		RK 25/6 - no longer available
Electrical data	Input	
	Input rated voltage	2 x 115 V
	Low-inrush current	16-times
	Rated frequency	50 - 60 Hz
	Output	
	Efficiency	82.0 %
	No-load loss (typ.)	0.50 W
	No-load voltage (app. x factor)	1.20
	Output rated voltage	2 x 6 V
	Rated Power	25.0 VA
	Approvals	
	Approvals	UL, C-UL
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Insulation class	A
	Protection index	IP 00
	Safety class (prepared)	II
	Test voltage	4000 V, 50 Hz
	Type	Open type
Catalogue logic		
Order numbers		
Order Number	RK 25/6 - no longer available	

Type		RK 25/6 - no longer available
Mechanical data	Terminal and mounting	
	Fixing method	Central connection by bolt
	Fixing screws	M5
	Terminals	leads
	Measures and weights	
	Diameter Ø	68 mm
	Weight	0.40 kg

Subject to change.