

## Toroidal safety isolating and isolating transformer RK Range **RK 25/9 - no longer available**



RK 100/25

### Standards

#### Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

#### Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

#### Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

### Approvals

UL 5085-1/-2, CSA 22.2 No.66



## Toroidal safety isolating and isolating transformer RK Range **RK 25/9 - no longer available**

Type		RK 25/9 - no longer available
<b>Electrical data</b>	<b>Input</b>	
	Input rated voltage	2 x 115 V
	Low-inrush current	16-times
	Rated frequency	50 - 60 Hz
	<b>Output</b>	
	Efficiency	82.0 %
	No-load loss (typ.)	0.50 W
	No-load voltage (app. x factor)	1.20
	Output rated voltage	2 x 9 V
	Rated Power	25.0 VA
	<b>Approvals</b>	
	Approvals	UL, C-UL
	<b>Environment</b>	
	Ambient temperature max.	40 °C
	<b>Safety and protection</b>	
	Insulation class	A
	Protection index	IP 00
	Safety class (prepared)	II
	Test voltage	4000 V, 50 Hz
	Type	Open type
<b>Catalogue logic</b>		
<b>Order numbers</b>		
<b>Order Number</b>	<b>RK 25/9 - no longer available</b>	

Type		RK 25/9 - no longer available
<b>Mechanical data</b>	<b>Terminal and mounting</b>	
	Fixing method	Central connection by bolt
	Fixing screws	M5
	Terminals	leads
	<b>Measures and weights</b>	
	Diameter Ø	68 mm
	Weight	0.40 kg

Subject to change.