

Toroidal safety isolating and isolating transformer RK Range
RK 40/15 - no longer available



RK 100/25

Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 40/15 - no longer available**

Type	RK 40/15 - no longer available
Electrical data	
Input	
Input rated voltage	2 x 115 V
Low-inrush current	13-times
Rated frequency	50 - 60 Hz
Output	
Efficiency	84.0 %
No-load loss (typ.)	0.60 W
No-load voltage (app. x factor)	1.18
Output rated voltage	2 x 15 V
Rated Power	40.0 VA
Approvals	
Approvals	UL, C-UL
Environment	
Ambient temperature max.	40 °C
Safety and protection	
Insulation class	A
Protection index	IP 00
Safety class (prepared)	II
Test voltage	4000 V, 50 Hz
Type	Open type
Catalogue logic	
Order numbers	
Order Number	RK 40/15 - no longer available

Type	RK 40/15 - no longer available
Mechanical data	
Terminal and mounting	
Fixing method	Central connection by bolt
Fixing screws	M5
Terminals	leads
Measures and weights	
Diameter Ø	80 mm
Weight	0.45 kg