

Toroidal safety isolating and isolating transformer RK Range **RK 40/22 - no longer available**



Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 40/22 - no longer available**

| Type | | RK 40/22 - no longer available | |
|-------------------------|---------------------------------------|--------------------------------|--|
| Electrical data | Input | | |
| | Input rated voltage | 2 x 115 V | |
| | Low-inrush current | 13-times | |
| | Rated frequency | 50 - 60 Hz | |
| | Output | | |
| | Efficiency | 84.0 % | |
| | No-load loss (typ.) | 0.60 W | |
| | No-load voltage (app. x factor) | 1.18 | |
| | Output rated voltage | 2 x 22 V | |
| | Rated Power | 40.0 VA | |
| | Approvals | | |
| | Approvals | UL, C-UL | |
| | Environment | | |
| | Ambient temperature max. | 40 °C | |
| | Safety and protection | | |
| | Insulation class | A | |
| | Protection index | IP 00 | |
| Safety class (prepared) | II | | |
| Test voltage | 4000 V, 50 Hz | | |
| Type | Open type | | |
| Catalogue logic | | | |
| Order numbers | | | |
| Order Number | RK 40/22 - no longer available | | |

| Type | | RK 40/22 - no longer available | |
|------------------------|------------------------------|--------------------------------|--|
| Mechanical data | Terminal and mounting | | |
| | Fixing method | Central connection by bolt | |
| | Fixing screws | M5 | |
| | Terminals | leads | |
| | Measures and weights | | |
| | Diameter Ø | 80 mm | |
| Weight | 0.45 kg | | |

Subject to change.