

## Toroidal safety isolating and isolating transformer RK Range **RK 63/18 - no longer available**



### Standards

#### Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

#### Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

#### Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

### Approvals

UL 5085-1/-2, CSA 22.2 No.66



## Toroidal safety isolating and isolating transformer RK Range **RK 63/18 - no longer available**

Type		RK 63/18 - no longer available		
Electrical data	Type			RK 63/18 - no longer available
	Input			
	Input rated voltage	2 x 115 V		
	Low-inrush current	17-times		
	Rated frequency	50 - 60 Hz		
	Output			
	Efficiency	86.0 %		
	No-load loss (typ.)	1.00 W		
	No-load voltage (app. x factor)	1.15		
	Output rated voltage	2 x 18 V		
	Rated Power	63.0 VA		
	Approvals			
	Approvals	UL, C-UL		
	Environment			
	Ambient temperature max.	40 °C		
	Safety and protection			
	Insulation class	A		
Protection index	IP 00			
Safety class (prepared)	II			
Test voltage	4000 V, 50 Hz			
Type	Open type			
Catalogue logic				
Order numbers				
Order Number	RK 63/18 - no longer available			
Mechanical data	Type			RK 63/18 - no longer available
	Terminal and mounting			
	Fixing method	Central connection by bolt		
	Fixing screws	M6		
	Terminals	leads		
	Measures and weights			
	Diameter Ø	90 mm		
Weight	0.75 kg			