

Toroidal safety isolating and isolating transformer RK Range **RK 63/6 - no longer available**



Standards

Mains transformer

to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Safety isolating transformer

to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Isolating transformer

to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66



Toroidal safety isolating and isolating transformer RK Range **RK 63/6 - no longer available**

Type		RK 63/6 - no longer available	
Electrical data	Input		
	Input rated voltage	2 x 115 V	
	Low-inrush current	17-times	
	Rated frequency	50 - 60 Hz	
	Output		
	Efficiency	86.0 %	
	No-load loss (typ.)	1.00 W	
	No-load voltage (app. x factor)	1.15	
	Output rated voltage	2 x 6 V	
	Rated Power	63.0 VA	
	Approvals		
	Approvals	UL, C-UL	
	Environment		
	Ambient temperature max.	40 °C	
	Safety and protection		
	Insulation class	A	
Protection index	IP 00		
Safety class (prepared)	II		
Test voltage	4000 V, 50 Hz		
Type	Open type		
Catalogue logic			
Order numbers			
Order Number	RK 63/6 - no longer available		

Type		RK 63/6 - no longer available	
Mechanical data	Terminal and mounting		
	Fixing method	Central connection by bolt	
	Fixing screws	M6	
	Terminals	leads	
	Measures and weights		
	Diameter Ø	90 mm	
Weight	0.75 kg		

Subject to change.